

APPLICATION FOR UNITED STATES LETTERS PATENT

of

Jipin Zhong and David Greenspan

for

BIOACTIVE SOL-GEL COMPOSITIONS AND METHODS

"Express Mail" mailing label No. EI331249039US
Date of Deposit 1-13-98

I hereby certify that this paper or fee
is being deposited with the United States
Postal Service "Express Mail Post Office to
Addressee" service under 37 CFR 1.10 on
the date indicated above and is addressed to
the Commissioner of Patents and Trademarks,
Washington, D.C. 20231.

Heather L. Rattelade

(Typed or printed name of person mailing
paper or fee)

Heather L. Rattelade
(Signature of person mailing paper or fee)

BURNS, DOANE, SWECKER & MATHIS, L.L.P.
P.O. Box 1404
Alexandria, Virginia 22313-1404
(919) 941-9240
Attorney Docket No: 028870-056

RECORDED - DEEDS DEPARTMENT

BIOACTIVE SOL-GEL COMPOSITIONS AND METHODS

FIELD OF THE INVENTION

End P.M.

The present invention relates to bioactive glass compositions, for example, used for filling bone defects, and bioactive compositions produced by a sol-gel process. The present invention also relates to various methods for making sol-gel bioactive glasses and methods of treatment using bioactive glasses.

5

BACKGROUND OF THE INVENTION

Sol-gel processes for making bioactive glass using sol-gel technology are generally known. For example, U.S. Patent No. 5,074,916 (the "916 patent"), the subject matter of which is incorporated herein by reference, discloses sol-gel processing techniques used to produce alkali-free bioactive glass compositions based on SiO₂, CaO and P₂O₅. The '916 patent discloses that by varying the SiO₂ content, a range of hydroxyapatite production rates can be obtained. Also, varying the time of exposure to actual or simulated in vivo solutions permits use of a range of allowable proportions of SiO₂. The sol-gel derived compositions disclosed in the '916 patent can be chosen to achieve target values for a thermal expansion coefficient, elastic modulus and volume electrical resistivity.

10

15

The processes and compositions described in U.S. Patent No. 5,074,916 have certain disadvantages. For example, the process of the '916 patent does not provide for bioactive glasses having large pore sizes. This results in a relatively low rate of

00000000000000000000000000000000

hydroxycarbonate apatite ("HCA") development when the glasses are exposed to biological fluids and tissues. See "Effect of Texture on the Rate of Hydroxyapatite Formation on Gel-Silica Interface", J. Am. Ceram. Soc., 78[9] 2463-68 (1995), the subject matter of which is herein incorporated by reference. Moreover, the resultant product lacks homogeneity, stability and can only be heated to a limited extent during preparation. Also, the resultant product lacks an acceptable level of resorbability.

Other examples of sol-gel processes can be found in Thomas, "Multicomponent Glasses From the Sol-Gel Process", Noyes Publications edited by Lisa C. Klein of the Center for Ceramics Research, College of Engineering, Rutgers, Piscataway, New Jersey and "Sol-Gel Science - The Physics and Chemistry of Sol-Gel processing, Brinker et al., Academic Press Inc. These publication are also incorporated by reference.

Previous methods for preparing monoliths of bioactive glasses have also proven unsatisfactory. Earlier methods required the use of various toxic chemicals in an effort to avoid cracking of the monolith during drying. U.S. Patent No. 4,849,378 ("the 378 patent"), incorporated herein by reference discloses a method of fabricating an ultraporous silicon dioxide containing gel monolith having a predetermined mean pore size by controlling temperature, duration and other conditions of aging. The '378 patent discloses that the use of a drying control chemical additive is important and formamide is the additive of choice. Similarly, U.S. Patent No. 4,851,150 ("the '150 patent") addresses drying control chemical additives for rapid production of large sol-gel derived monoliths. The '150 patent also discloses drying in a methanolic atmosphere. Both of these methods are unsatisfactory because they require the use of chemical additives.

Other early work in U.S. Patent No. 5,076,980 (incorporated by reference) used drying under humidity environment and sintering under some gas atmosphere to make a

RECEIVED: DEPOG 60

sol-gel monolith. However, the focus of such procedures was the fabrication of crack-free and fully dense silica glass and the pore texture of the monolith was not mentioned. Moreover, this patent does not address the preparation of a bioactive glass.

Accordingly, it is an object of the present invention to provide a sol-gel process, particle and monolith that yield bioactive glasses used for bone grafting and filling osseous defects, having larger pore size at a given level of silicon dioxide in the final composition, faster HCA formation, better resorbability, and better homogeneity. It is further an object of the present invention to provide for precise control of rates of resorbtion.

SUMMARY OF THE INVENTION

The present invention is directed to a process for making bioactive glasses used, for example, for bone grafting including; preparing a reaction mixture (sol) capable of forming a gel, aging the reaction mixture, near equilibrium drying a gel resulting from the reaction mixture, and heating the near equilibrium-dried gel. The present invention is also directed to dried bioactive glass compositions and monolithic bioactive compositions having improved resorbability. The present invention is further directed to materials suitable for bone grafting, repairing of tissue defects and other orthopedic uses.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGURE 1 Surgically created defect 8 weeks post-op. Very little bone formation noted.

FIGURE 2 Melt derived 45S5 Bioglass® at 4 weeks. Red stains show bone formation throughout the defect, especially around particles near the edges of the defect (arrow).

FIGURE 3 Melt derived 45S5 Bioglass® at 8 weeks, showing dramatic increase in bond formation, evenly throughout defect. Some resorption of particles is occurring.

FIGURE 4 58S sol-gel glass produced by near-equilibrium drying at 4 weeks post-op. Rapid bone formation is noted even in the center of the defect (solid arrows). Resorption of many particles can already be seen (open arrows).

FIGURE 5 58S sol-gel glass at 8 weeks. Extensive bond formation is noted throughout the defect. Most of the particles have already resorbed, and are replaced by newly maturing trabecular bone.

FIGURE 6 77S sol-gel produced by near-equilibrium drying at 4 weeks post-op. Bone formation is present, but not as extensive as in 58S glass. Arrows indicate resorption of some particles.

FIGURE 7 77S sol-gel glass produced by near-equilibrium drying at 8 weeks. Bone formation has proceeded to the center of the defect (red stained regions). About 50% of the particles have resorbed.

FIGURE 8 58S sol-gel glass at 8 weeks post-op. Red stained region shows extensive bone formation around and even inside a particle which is clearly resorbing (region labeled at "A"). No inflammatory response is noted.

5

FIGURE 9 77S sol-gel glass at 8 weeks post-op. Bone is noted surrounding particles with no inflammatory response. Resorption of particles can be noted (arrows) although it is slower than in the 58S sol-gel glass.

FIGURE 10 FTIR spectra of various sol-gel bioactive glass compositions.

All have formed extensive HCA layers.

10

FIGURE 11(A) FTIR spectra of sol-gel bioactive glass prepared by previous method A.

FIGURE 11(B) FTIR spectra of sol-gel bioactive glass made in accordance with the present invention including a near equilibrium drying step. As seen in the spectra, more rapid formation of HCA is observed when near equilibrium drying is used.

15

FIGURE 12 FTIR spectra of sol-gel bioactive glass monolith after 24 hours in SBF using near equilibrium drying.

FIGURE 13 An example of a drying schedule showing temperature vs. time in standard vs. near equilibrium drying schedules.

BEEFTO-000000000000

FIGURE 14 Example of a heating schedule showing temperature vs. time.

FIGURE 15 Silica release of particle prepared in accordance with the present invention vs. a previous sol-gel method disclosed in the '916 patent.

5

FIGURE 16 Diagram of average pore size vs. drying temperature.

FIGURE 17 A phase diagram of water.

FIGURE 18 Ion release of 77(s) in SBF.

FIGURE 19 Si release of 77S(B) in SBF.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000
1005
1010
1015
1020
1025
1030
1035
1040
1045
1050
1055
1060
1065
1070
1075
1080
1085
1090
1095
1100
1105
1110
1115
1120
1125
1130
1135
1140
1145
1150
1155
1160
1165
1170
1175
1180
1185
1190
1195
1200
1205
1210
1215
1220
1225
1230
1235
1240
1245
1250
1255
1260
1265
1270
1275
1280
1285
1290
1295
1300
1305
1310
1315
1320
1325
1330
1335
1340
1345
1350
1355
1360
1365
1370
1375
1380
1385
1390
1395
1400
1405
1410
1415
1420
1425
1430
1435
1440
1445
1450
1455
1460
1465
1470
1475
1480
1485
1490
1495
1500
1505
1510
1515
1520
1525
1530
1535
1540
1545
1550
1555
1560
1565
1570
1575
1580
1585
1590
1595
1600
1605
1610
1615
1620
1625
1630
1635
1640
1645
1650
1655
1660
1665
1670
1675
1680
1685
1690
1695
1700
1705
1710
1715
1720
1725
1730
1735
1740
1745
1750
1755
1760
1765
1770
1775
1780
1785
1790
1795
1800
1805
1810
1815
1820
1825
1830
1835
1840
1845
1850
1855
1860
1865
1870
1875
1880
1885
1890
1895
1900
1905
1910
1915
1920
1925
1930
1935
1940
1945
1950
1955
1960
1965
1970
1975
1980
1985
1990
1995
2000
2005
2010
2015
2020
2025
2030
2035
2040
2045
2050
2055
2060
2065
2070
2075
2080
2085
2090
2095
2100
2105
2110
2115
2120
2125
2130
2135
2140
2145
2150
2155
2160
2165
2170
2175
2180
2185
2190
2195
2200
2205
2210
2215
2220
2225
2230
2235
2240
2245
2250
2255
2260
2265
2270
2275
2280
2285
2290
2295
2300
2305
2310
2315
2320
2325
2330
2335
2340
2345
2350
2355
2360
2365
2370
2375
2380
2385
2390
2395
2400
2405
2410
2415
2420
2425
2430
2435
2440
2445
2450
2455
2460
2465
2470
2475
2480
2485
2490
2495
2500
2505
2510
2515
2520
2525
2530
2535
2540
2545
2550
2555
2560
2565
2570
2575
2580
2585
2590
2595
2600
2605
2610
2615
2620
2625
2630
2635
2640
2645
2650
2655
2660
2665
2670
2675
2680
2685
2690
2695
2700
2705
2710
2715
2720
2725
2730
2735
2740
2745
2750
2755
2760
2765
2770
2775
2780
2785
2790
2795
2800
2805
2810
2815
2820
2825
2830
2835
2840
2845
2850
2855
2860
2865
2870
2875
2880
2885
2890
2895
2900
2905
2910
2915
2920
2925
2930
2935
2940
2945
2950
2955
2960
2965
2970
2975
2980
2985
2990
2995
3000
3005
3010
3015
3020
3025
3030
3035
3040
3045
3050
3055
3060
3065
3070
3075
3080
3085
3090
3095
3100
3105
3110
3115
3120
3125
3130
3135
3140
3145
3150
3155
3160
3165
3170
3175
3180
3185
3190
3195
3200
3205
3210
3215
3220
3225
3230
3235
3240
3245
3250
3255
3260
3265
3270
3275
3280
3285
3290
3295
3300
3305
3310
3315
3320
3325
3330
3335
3340
3345
3350
3355
3360
3365
3370
3375
3380
3385
3390
3395
3400
3405
3410
3415
3420
3425
3430
3435
3440
3445
3450
3455
3460
3465
3470
3475
3480
3485
3490
3495
3500
3505
3510
3515
3520
3525
3530
3535
3540
3545
3550
3555
3560
3565
3570
3575
3580
3585
3590
3595
3600
3605
3610
3615
3620
3625
3630
3635
3640
3645
3650
3655
3660
3665
3670
3675
3680
3685
3690
3695
3700
3705
3710
3715
3720
3725
3730
3735
3740
3745
3750
3755
3760
3765
3770
3775
3780
3785
3790
3795
3800
3805
3810
3815
3820
3825
3830
3835
3840
3845
3850
3855
3860
3865
3870
3875
3880
3885
3890
3895
3900
3905
3910
3915
3920
3925
3930
3935
3940
3945
3950
3955
3960
3965
3970
3975
3980
3985
3990
3995
4000
4005
4010
4015
4020
4025
4030
4035
4040
4045
4050
4055
4060
4065
4070
4075
4080
4085
4090
4095
4100
4105
4110
4115
4120
4125
4130
4135
4140
4145
4150
4155
4160
4165
4170
4175
4180
4185
4190
4195
4200
4205
4210
4215
4220
4225
4230
4235
4240
4245
4250
4255
4260
4265
4270
4275
4280
4285
4290
4295
4300
4305
4310
4315
4320
4325
4330
4335
4340
4345
4350
4355
4360
4365
4370
4375
4380
4385
4390
4395
4400
4405
4410
4415
4420
4425
4430
4435
4440
4445
4450
4455
4460
4465
4470
4475
4480
4485
4490
4495
4500
4505
4510
4515
4520
4525
4530
4535
4540
4545
4550
4555
4560
4565
4570
4575
4580
4585
4590
4595
4600
4605
4610
4615
4620
4625
4630
4635
4640
4645
4650
4655
4660
4665
4670
4675
4680
4685
4690
4695
4700
4705
4710
4715
4720
4725
4730
4735
4740
4745
4750
4755
4760
4765
4770
4775
4780
4785
4790
4795
4800
4805
4810
4815
4820
4825
4830
4835
4840
4845
4850
4855
4860
4865
4870
4875
4880
4885
4890
4895
4900
4905
4910
4915
4920
4925
4930
4935
4940
4945
4950
4955
4960
4965
4970
4975
4980
4985
4990
4995
5000
5005
5010
5015
5020
5025
5030
5035
5040
5045
5050
5055
5060
5065
5070
5075
5080
5085
5090
5095
5100
5105
5110
5115
5120
5125
5130
5135
5140
5145
5150
5155
5160
5165
5170
5175
5180
5185
5190
5195
5200
5205
5210
5215
5220
5225
5230
5235
5240
5245
5250
5255
5260
5265
5270
5275
5280
5285
5290
5295
5300
5305
5310
5315
5320
5325
5330
5335
5340
5345
5350
5355
5360
5365
5370
5375
5380
5385
5390
5395
5400
5405
5410
5415
5420
5425
5430
5435
5440
5445
5450
5455
5460
5465
5470
5475
5480
5485
5490
5495
5500
5505
5510
5515
5520
5525
5530
5535
5540
5545
5550
5555
5560
5565
5570
5575
5580
5585
5590
5595
5600
5605
5610
5615
5620
5625
5630
5635
5640
5645
5650
5655
5660
5665
5670
5675
5680
5685
5690
5695
5700
5705
5710
5715
5720
5725
5730
5735
5740
5745
5750
5755
5760
5765
5770
5775
5780
5785
5790
5795
5800
5805
5810
5815
5820
5825
5830
5835
5840
5845
5850
5855
5860
5865
5870
5875
5880
5885
5890
5895
5900
5905
5910
5915
5920
5925
5930
5935
5940
5945
5950
5955
5960
5965
5970
5975
5980
5985
5990
5995
6000
6005
6010
6015
6020
6025
6030
6035
6040
6045
6050
6055
6060
6065
6070
6075
6080
6085
6090
6095
6100
6105
6110
6115
6120
6125
6130
6135
6140
6145
6150
6155
6160
6165
6170
6175
6180
6185
6190
6195
6200
6205
6210
6215
6220
6225
6230
6235
6240
6245
6250
6255
6260
6265
6270
6275
6280
6285
6290
6295
6300
6305
6310
6315
6320
6325
6330
6335
6340
6345
6350
6355
6360
6365
6370
6375
6380
6385
6390
6395
6400
6405
6410
6415
6420
6425
6430
6435
6440
6445
6450
6455
6460
6465
6470
6475
6480
6485
6490
6495
6500
6505
6510
6515
6520
6525
6530
6535
6540
6545
6550
6555
6560
6565
6570
6575
6580
6585
6590
6595
6600
6605
6610
6615
6620
6625
6630
6635
6640
6645
6650
6655
6660
6665
6670
6675
6680
6685
6690
6695
6700
6705
6710
6715
6720
6725
6730
6735
6740
6745
6750
6755
6760
6765
6770
6775
6780
6785
6790
6795
6800
6805
6810
6815
6820
6825
6830
6835
6840
6845
6850
6855
6860
6865
6870
6875
6880
6885
6890
6895
6900
6905
6910
6915
6920
6925
6930
6935
6940
6945
6950
6955
6960
6965
6970
6975
6980
6985
6990
6995
7000
7005
7010
7015
7020
7025
7030
7035
7040
7045
7050
7055
7060
7065
7070
7075
7080
7085
7090
7095
7100
7105
7110
7115
7120
7125
7130
7135
7140
7145
7150
7155
7160
7165
7170
7175
7180
7185
7190
7195
7200
7205
7210
7215
7220
7225
7230
7235
7240
7245
7250
7255
7260
7265
7270
7275
7280
7285
7290
7295
7300
7305
7310
7315
7320
7325
7330
7335
7340
7345
7350
7355
7360
7365
7370
7375
7380
7385
7390
7395
7400
7405
7410
7415
7420
7425
7430
7435
7440
7445
7450
7455
7460
7465
7470
7475
7480
7485
7490
7495
7500
7505
7510
7515
7520
7525
7530
7535
7540
7545
7550
7555
7560
7565
7570
7575
7580
7585
7590
7595
7600
7605
7610
7615
7620
7625
7630
7635
7640
7645
7650
7655
7660
7665
7670
7675
7680
7685
7690
7695
7700
7705
7710
7715
7720
7725
7730
7735
7740
7745
7750
7755
7760
7765
7770
7775
7780
7785
7790
7795
7800
7805
7810
7815
7820
7825
7830
7835
7840
7845
7850
7855
7860
7865
7870
7875
7880
7885
7890
7895
7900
7905
7910
7915
7920
7925
7930
7935
7940
7945
7950
7955
7960
7965
7970
7975
7980
7985
7990
7995
8000
8005
8010
8015
8020
8025
8030
8035
8040
8045
8050
8055
8060
8065
8070
8075
8080
8085
8090
8095
8100
8105
8110
8115
8120
8125
8130
8135
8140
8145
8150
8155
8160
8165
8170
8175
8180
8185
8190
8195
8200
8205
8210
8215
8220
8225
8230
8235
8240
8245
8250
8255
8260
8265
8270
8275
8280
8285
8290
8295
8300
8305
8310
8315
8320
8325
8330
8335
8340
8345
8350
8355
8360
8365
8370
8375
8380
8385
8390
8395
8400
8405
8410
8415
8420
8425
8430
8435
8440
8445
8450
8455
8460
8465
8470
8475
8480
8485
8490
8495
8500
8505
8510
8515
8520
8525
8530
8535
8540
8545
8550
8555
8560
8565
8570
8575
8580
8585
8590
8595
8600
8605
8610
8615
8620
8625
8630
8635
8640
8645
8650
8655
8660
8665
8670
8675
8680
8685
8690
8695
8700
8705
8710
8715
8720
8725
8730
8735
8740
8745
8750
8755
8760
8765
8770
8775
8780
8785
8790
8795
8800
8805
8810
8815
8820
8825
8830
8835
8840
8845
8850
8855
8860
8865
8870
8875
8880
8885
8890
8895
8900
8905
8910
8915
8920
8925
8930
8935
8940
8945
8950
8955
8960
8965
8970
8975
8980
8985
8990
8995
9000
9005
9010
9015
9020
9025
9030
9035
9040
9045
9050
9055
9060
9065
9070
9075
9080
9085
9090
9095
9100
9105
9110
9115
9120
9125
9130
9135
9140
9145
9150
9155
9160
9165
9170
9175
9180
9185
9190
9195
9200
9205
9210
9215
9220
9225
9230
9235
9240
9245
9250
9255
9260
9265
9270
9275
9280
9285
9290
9295
9300
9305
9310
9315
9320
9325
9330
9335

	<chem>SiO2</chem>	-	40 - 90
	<chem>CaO</chem>	-	.4 - 45
	<chem>Na2O</chem>	-	0 - 10
	<chem>P2O5</chem>	-	2 - 16
5	<chem>CaF2</chem>	-	0 - 25
	<chem>B2O3</chem>	-	0 - 4
	<chem>K2O</chem>	-	0 - 8
	<chem>MgO</chem>	-	0 - 5

The process of the present invention includes a drying step which is not included in earlier processes. It has unexpectedly been determined that the use of near-equilibrium drying in place of or in addition to drying under dry conditions used in prior processes provides for much larger average pore size in the final composition at a given level of SiO2 than previously known. It was unexpectedly found that a near equilibrium drying resulted in larger pore size and a higher rate of resorption.

Near-equilibrium drying is drying under the conditions near the two phase boundaries in the phase diagram at a temperature and pressure sufficient to yield a bioactive glass with large pore structure i.e. a pore structure sufficient to yield a bioactive glass. For example, near equilibrium drying may be drying under the conditions near the line in the phase diagram of water as shown in Fig. 17 (or other liquids such as methanol, ethanol, acetone, liquid CO2, benzene and so on). By manipulating the sealing of the designed drying chamber to adjust the extent of the drying condition away from the equilibrium line and relative humidity (from environment humidity to 98%), the duration of near-equilibrium drying, and the temperature at which the drying is conducted, one can

RECEIVED - DECEMBER 60

5

drastically alter pore size of resultant bioactive glass. For example, increasing the sealing of the drying chamber during drying typically results in an increase in relative humidity and pore diameter. Near-equilibrium drying temperature can also be varied, for example, as depicted in Figure 13 for the case of water drying. If using other liquids mentioned above than water, one may obtain a faster drying or increase the pore size range of the gel to a large extent.

By manipulating the percentage humidity, the duration of near equilibrium drying, and the temperature at which near equilibrium drying is conducted, one can drastically alter pore size of the resultant bioactive glass. For example, increasing the level of humidity during drying typically results in an increase in pore diameter. Near equilibrium drying temperatures can also be varied, for example, as depicted in Figure 13. It was unexpected that the change in drying temperature should give rise to such a large change in pore structure and an increase in resorbability.

10
15
20

A sol-gel process in accordance with the present invention is any process that includes the use of a sol-gel in the preparation of bioactive glass. For example, a reaction mixture including tetraethoxysilane (TEOS), triethylphosphate (TEP), and calcium nitrate can be used to make sol-gel bioactive glasses. Alkoxides of calcium, titanium, zirconium, magnesium aluminum, iron and potassium can also be used. Other appropriate ingredients will also be apparent to those of ordinary skill in the art. The present invention also contemplates the use of aerogels. When an aerogel is used, increased pressure is used instead of near equilibrium drying to achieve larger pore size and greater resorbability.

Sol-gel processing in accordance with the present invention includes a near equilibrium drying step which yields larger pore size in the final product and permits

development of HCA very rapidly for both high and low silicon dioxide content gels.

Indeed, compositions in accordance with the present invention form HCA more rapidly

than prior gels when exposed to SBF (Simulated Body Fluid, Kokubo, T. et al., J.

Biomed. Mater. Res., 24, 721-34, 1990) or physiological fluids. The near equilibrium

5 drying technique of the present invention also provides for more homogeneous gels which
can be heated to higher temperatures than previous gels while retaining large pore
diameter. This permits much better control of the final product e.g. resorbability,
homogeneity and physical structure. For example, previous sol-gel compositions were
not able to provide adequate resorbability at higher levels of silicon dioxide.

10 Surprisingly, the present invention provides for excellent resorbability even when high
amounts of silicon dioxide are included. The sol-gel glasses of the present invention are
also more homogeneous than prior sol-gel glasses and calcium is distributed uniformly.

The process of the present invention also provides for bioactive glass capable of
resorbing more quickly than known sol-gel bioactive glass materials. For example,
15 in-vivo testing of one embodiment of the present invention showed that more than 50% of
sol-gel material made in accordance with the process of the present invention resorbed at
eight weeks (see Figures 5, 7, 8 and 9). Comparable prior 45S5 melt derived bioactive
glasses, as described in the '916 patent which allow bone ingrowth to about the same
extent, have not resorbed at all by eight weeks. Indeed, the '916 patent indicates glasses
20 including more than 55% silicon dioxide are not bioactive. Moreover, bioactive glass
made by the process of the present invention also exhibits substantially no unwanted
inflammatory response.

RECEIVED : DESENCO

The drying technique of the present invention can be used to prepare all types of sol-gel bioactive glasses. For example, the process of the present invention can be used to prepare frit, monoliths, powders, coatings, fibers, mats, weaves and composites.

Generally, frit, monoliths, powders, and coatings can be derived from sol-gel processing. Frit can be ground to very broad ranges of particle size such as from about 2 μm up to 1 mm for any purpose. The monolith can be formed to complex shapes such as various implants. Powders can be made to spherical form and from submicron to a few hundred microns. Such compositions are useful, for example, in bone repair and other orthopedic applications, drug delivery, treating tooth hypersensitivity as well as the remineralization of tooth structure, burn healing, and wound healing.

While not being bound to any particular theory, it is believed that the near-equilibrium drying step reduces capillary force inside the pore structure of the gel which results in large pore size. Gels are networks of small colloid particles. The networks includes voids which become pores and pore channels in the final glass composition. It is believed that the moisture of the near-equilibrium drying step enhances the reaction at the neck between two particles in the network and the strength of the neck and "back bone" of the gel structure which reduces shrinkage of the drying structure and ultimately results in gels with large pores.

On the other hand, due to the liquid tension, the pressure difference between the different size of pores and channels is:

$$\Delta P = 2\gamma \cos\theta / r$$

where, γ is liquid tension, θ is contact angle and r is the radius of pores and pore channels. During drying, the pressure difference, ΔP , will pull the network tight enabling

pore collapse and gel shrinkage as liquid evaporates. It is believed that near-equilibrium drying allows the liquid inside the pore structure to evaporate under the condition of near-equilibrium at any temperature in Fig. 13. This keeps liquid vapor pressure inside the channels and pores at high heating conditions which resists the shrinkage and collapse of the gel structure and results in large pore sizes.

5

The following examples are included for purposes of illustration only. They are not intended to narrow the scope of the claims in any way.

Example I - Preparation of Sol-gel Frit

The preparation of sol-gel bioactive glass frit was accomplished as follows:

10

First, a reaction mixture of deionized water, TEOS, TEP, and calcium nitrate was prepared. Deionized water and hydrochloric acid solutions were combined in a large reactor container. The container was placed on a stirring plate and the solution was stirred using a magnetic stirring bar at medium speed. Then, TEOS was poured into the container and allowed to mix until the solution went clear. The mole ratio of water vs. the mole ratio of TEOS was 4 (other mole ratios can be used e.g. 2 - 16). After 30 minutes, TEP was added to the stirring solution. In another 20 minutes, calcium nitrate was added. The solution was then stirred for an additional hour then followed by the below steps to make frit:

15

- a. The reaction mixture was transferred to large containers and the containers were placed in an oven for aging at 60°C for 54 hours;

20

RECORDED DECODED

b. Pore liquor was removed and the aged gels were transferred into a large drying vessel and the vessel was placed inside a designed drying chamber with a proper amount of water. Then, the whole chamber was placed into an oven and dried under the drying schedule in Figure 13;

- 5 c. The dried gels were then heated in a large quartz crucible using the heating schedule of Figure 14;
- d. After drying and heating, the gel cracks and forms large granules. The granules can then be ground to form frit and then separated into various size ranges thus obtained.

10 The following compositions were prepared by a process including a near equilibrium drying step:

	Sample ID	Si mol%(wt%)	Ca mol%(wt%)	P mol%(wt%)
	77S	80 (77)	16 (14)	4 (9)
	68S	70 (68)	26 (23)	4 (9)
15	58S	60 (58)	36 (33)	4 (9)

The foregoing compositions were prepared from reaction mixtures prepared as follows:

Sample 77S:

	1) D.I. Water:	Xx237 ml	
	2) HCl (2N):	Xx44.89 ml	mix 10 minutes
	3) TEOS (Si(OC ₂ H ₅) ₄):	Xx667 ml	mix 30 minutes
	4) TEP (OP(OC ₂ H ₅) ₃):	Xx51 ml	mix 20 minutes
5	5) Ca(NO ₃) ₂ *4H ₂ O:	X x 141.24 g	mix 60 minutes

Sample 68S

-141X	1) D.I. Water:	Xx238.66 ml	
	2) HCl (2N):	Xx39.78 ml	mix 10 minutes
	3) TEOS (Si(OC ₂ H ₅) ₄):	Xx663.55 ml	mix 30 minutes
10	4) TEP (OP(OC ₂ H ₅) ₃):	Xx58 ml	mix 20 minutes
	5) Ca(NO ₃) ₂ *4H ₂ O:	Xx260.93 g	mix 60 minutes

Sample 58S

-141X	1) D.I. Water:	Xx377.42 ml	
	2) HCl (2N):	Xx62.28 ml	mix 10 minutes
15	3) TEOS (Si(OC ₂ H ₅) ₄)	Xx511.19 ml	mix 30 minutes
	4) TEP (OP(OC ₂ H ₅) ₃):	Xx52.10 ml	mix 20 minutes
	5) Ca(NO ₃) ₂ *4H ₂ O:	Xx324.80 g	mix 60 minutes

X = Any factor to increase batch size.

x = multiply

As can be seen in Fig. 13, the drying temperature is 180°C for standard drying techniques and, in example, 130°C for near equilibrium drying of the present invention. The use of lower temperatures in near equilibrium drying maintains higher humidity for a longer period of time (gels can be humidity dried by steam injection into a drying oven).
5 Lower near equilibrium drying temperature also benefits the reaction between necks and strengthens structure.

Near equilibrium drying:

Total drying time was 72 hours as shown in fig. 13. The proper amount of water was placed in the oven to provide water vapor which maintained humidity around 98% in the first 60 hours at 60°C, 90°C and 130°C. In the last 12 hours at 130°C, the humidity was decreased gradually from 98% to ambient humidity as water evaporates out.
10

ELECTRO-IMAGING

Comparative Results:

The following results were obtained for near equilibrium dried samples made in accordance with the present invention with heating at 700°C:

<u>Sample</u>	<u>% SiO₂</u>	<u>Average Pore Diameter</u>	<u>Surface Area (M²/g)</u>
5 58S	60	86	207
68S	70	65	305
77S	80	40	389

The following results were obtained when the near equilibrium drying step of the present invention is omitted (the process of U.S. Patent No. 5,074,916) with heating at 700°C:

<u>Sample</u>	<u>% SiO₂</u>	<u>Average Pore Diameter</u>	<u>Surface Area (M²/g)</u>
58S	60	68	289
68S	70	50	326
77S	80	24 (30)	241(431)

() = sample heated at 600°C

As seen above, the near equilibrium drying step of the present invention provides for an unexpected increase in pore size. As further illustrated below, this results in a drastic and

unexpected improvement in bioactivity i.e. the ability to form HCA when exposed to *in vivo*.

In Vivo Bone Implantation

Figures 1-9 are photographs indicating the excellent results obtainable by the present invention when compared with other bioactive glasses when exposed in vitro or in vivo.
5 Figure 1 shows what a surgically created defect looks like 8 weeks post-op. Figures 2 and 3 show the results obtained when melt derived bioactive glasses are used. Figures 4-9 show the excellent results obtained by the sol-gel of the present invention. Figure 6 shows resorption in high silica content particles (80% by weight) after only 4 weeks in *in vivo*. Figure 7 shows 50% resorption of 80% silica content particles after only 8 weeks in *in vivo*. Even more dramatic results can be seen in Figures 4 and 5 which show extensive resorption in 60% by weight silica bioactive glass compositions after only 4 weeks in *in vivo* and very advanced resorption after only 8 weeks. This animal model included near equilibrium dried particles in accordance with the present invention of 300-800 microns as measured by optical spectroscopy. The photos of figures 1-9 are rights to histological
10 sections from the animal study.
15

In Vitro Exposure SBF

Other resorbability testing was also conducted on the foregoing comparative sol-gels.
20 0.2g of sol-gel bioactive glass particles of samples 77S(A) [no near equilibrium drying] and 77S(B) [equilibrium dried] were tested in 200 ml of SBF in a centerfuge at 175 RPM over a duration of 1hr, 6hrs, 20hrs, 7 days, 14 days and 28 days. Gel particles with large pore size show greater degradability than small pore size as demonstrated in

5

Figure 15. 77S(A) had an average pore diameter of 24 angstroms whereas 77S(B) had an average pore diameter of 40 angstroms. As shown in Figure 18, silica continues to leach from the glasses and calcium and phosphate precipitate back on the particles which simulates the events happening after implantation that induce bone growth while silica dissolves. The negative release of calcium and phosphorous in Figure 18 implies that calcium and phosphorous precipitate from solution to particles. Thirty percent by weight of silica has been lost in 4 weeks as shown in Figure 19 which means that these are certainly bioresorbable materials.

10

15

FTIR spectra are used to indicate the formation of HCA on the surface of bioactive glasses that have been exposed to simulated or real body fluids. Figure 10 shows that samples prepared by a process including near equilibrium drying developed HCA within 24 hours. Figures 11(A) and (B) show the FTIR spectra of 77S(A) in accordance with the '916 patent vs. 77S(B) made by a process including near equilibrium drying. It took 2 days to form HCA on the surface of the 77S(A) sample whereas it only took 14 hours to form HCA on the 77S(B) sample which included a near equilibrium drying step.

Example 2 - Preparation Of A Monolith

20

Monoliths must be prepared in a manner that minimizes crack formation. In order to accomplish the manufacture of monoliths of bioactive sol-gel glasses without cracks, others have prepared monoliths by drying under supercritical conditions (C. Jeffrey

Brinker, George W. Scherer, "Sol-Gel Science, the Physics and Chemistry of Sol-Gel Processing", Academic Press, 1990) or with chemical additives (L.L. Hench "Science of Ceramic Chemical Processing", pp. 52-64, Wiley 1986). In the present example, an inexpensive method, drying under near equilibrium conditions was used. Water vapor pressure associated with near equilibrium drying yields large pore gels and strengthens the backbone of colloid particle networks to prevent cracking during drying. The resultant bulk monoliths show great bioactivity as seen in Figure 12. Unlike drying under higher pressure supercritical conditions, near equilibrium drying does not require the use of expensive, complicated equipment. Bioactive aerogels can also be used to prepare monoliths by replacing the near equilibrium drying step with higher pressure. Near equilibrium drying also does not require the use of drying chemicals or high chemical removal temperatures as required by chemical drying additives.

Monoliths were prepared by the following process:

A reaction medium was prepared including deionized water, hydrochloric acid (2N), TEOS, TEP, and calcium nitrate. First, deionized water and hydrochloric acid were combined in a large reaction container and placed on a stirring plate. The solution was stirred using a magnetic stirring bar at medium speed. TEOS was then poured into the container and the solution was allowed to mix until clear. The mole ratio of water to TEOS was 4 (the mole ratio can be varied from, for example, 2 - 16). After 30 minutes, TEP was added to the stirring solution. In another 20 minutes, calcium nitrate was added. The solution was then stirred for an additional hour then followed by the following steps to make monoliths:

- a. The prepared solutions were cast into molds of desired shape and loosely sealed. The molds were then placed in a closed chamber with water for aging for a period of 1 - 7 days at room temperature;
- 5 b. The molds were then sealed tightly and placed in an oven for aging for 54 hours at 60°C;
- 10 c. The pore liquor was then removed from the molds and the shaped gel was quickly transferred into a large drying vessel with a loosely fit cover placed over it. Then, the vessel was placed inside a designed drying chamber with a proper amount of water and the whole chamber was placed into an oven and dried using the drying schedule in Figure 13;
- d. The dried gels were then heated in a quartz crucible using the heating schedule in Figure 14.

265770 "DE990060

11